



Family Owned Over 85 Years. We Care!

ABOVE GROUND TANK VALVES

SOLENOID VALVES

Application -

Reducing fire hazards and fuel spillage should a line rupture. The valve opens when energized from a dispenser or pump switch.

Part Number - 404V



UNIVERSAL Advantage

Heavy duty two way normally closed, one directional flow. Piston style design for High Flow, and zero differential.

Features -

- ✓ Zero Differential - Direct Lift
- ✓ Higher Flow than Diaphragm Valves
- ✓ Internal Pressure Relief
- ✓ No need to specify 120V/60 or 24V/DC when ordering

Construction -

- Brass Body & Piston
- FKM seals



Pipe Size (inch)	Part Number	Orifice Size (mm)	Cv Flow Factor	Operating Pressure Differential (PSI)		Max Fluid Temp (F)	Watt Rating/ Insulation	
				Min	Max		AC	DC
				1- 1/2"	404V-15-120/60-24DC	38	19	0
2"	404V-20-120/60-24DC	38	27	0	100	180	30/H	48H

Current Draw (amps):

Volt/Hz	120/60	24/DC
Holding	0.66	2.0
Inrush	2.23	2.0

Important Installation Instructions: A strainer or a filter (100 microns) is recommended to be installed as close as possible to the inlet of the valve. The valve can only be installed in the horizontal position with coil vertical and upright.

Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.

UNIVERSAL VALVE COMPANY

478 Schiller Street, Elizabeth, NJ 07206 • (800) 223-0741 • (908) 351-0606 • Fax: (908) 351-0369 • universalvalve.com

© 2020 Universal Valve Company, Inc.