



Family Owned Over 75 Years. We Care!

EXTRACTOR FITTINGS

EXTRACTABLE CHECK VALVES

Application -

Holds prime in suction system applications.

Part Number - 515



UNIVERSAL
Advantage


Strategically used in place of foot valves.
**ONLY UNIVERSAL HAS A
METAL-TO-METAL BRASS SEAL.**

Features -

- ✓ Holds the prime
- ✓ Easily serviced without disturbing existing pipes in suction systems
- ✓ No need to remove valve to clean because it has a removable front plate for easy maintenance
- ✓ Rugged cast iron body eliminates distortion of valve seat when tightened

Construction -

- Zinc plated cast iron body



Model	Thread Size	Weight (lbs.)	A	B	Seal
515B-15	1-1/2"	8.5	5-3/16"	4-7/8"	Buna-N
515BS-15	1-1/2"	8.5	5-3/16"	4-7/8"	Buna-N w/ strainer
515M-15	1-1/2"	8.5	5-3/16"	4-7/8"	Metal-to-Metal
515MS-15	1-1/2"	8.5	5-3/16"	4-7/8"	Metal-to-Metal w/strainer

Replacement Parts

Part Numbers	Description
0611V-34-B	5/16" Bolt
515-15-10	Cone Spring
515-15-7	Cover Gasket
515-15-8	Cage Gasket
515-15-9	Strainer
515-CAB	Cage Assembly (Buna-N)
515-CAM	Cage Assembly (Metal to Metal)

Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.

UNIVERSAL VALVE COMPANY

478 Schiller Street, Elizabeth, NJ 07206 • (800) 223-0741 • (908) 351-0606 • Fax: (908) 351-0369 • universalvalve.com

© 2009 Universal Valve Company, Inc.