SUMP COVER



UNIVERSAL SUMP RETROFIT COVER

Application -

Eliminates leaking polyethylene and fiberglass sump covers without breaking concrete.

Part Number - 1943



- ✓ Installs in minutes
- ✓ Rugged stainless steel ring and cover for maximum strength
- ✓ Mechanical seals insure maximum life and tightness
- ✓ Field Adjustable Clamping device
- ✓ Does not rely on glues or adhesives that deteriorate after 1 year
- ✓ An additional safety monitoring access cover (8") eliminates the need to remove the top cover, saving time and preventing injuries.
- Custom Sizes available.
- ✓ Optional straight sump design hardware available. (Suffux -S)

Construction -

- · Stainless Steel Standard
- Aluminum Rails

Model	Range of sump Openings	Inner Manway Id Opening Required	Height	Weight
1943-2128	20.5" to 28.5"	29.5"	3-1/4"	42lbs
1943-2533	25" to 33.5"	34"	3-1/4"	50lbs
1943-2734	27" to 34.75"	34-3/4"	3-1/4"	58lbs
1943-3240	32" to 40"	41"	3-1/4"	65lbs

^{*}Requires 5" or greater from the top of the sump riser to grade level manhole cover. Model 1943-2533 fits most 36" manways.



Only Universal's retrofit cover truly eliminates water leakage. Our DOUBLE SEAL design keeps your sumps completely dry!

> UST Regulations require that all of the components of a UST system be tested for "product tightness"



Replacement Parts

Part Numbers	Description		
1943-06-WHT	Monitor Cover/Ring Assembly		
1943-PK	Replacement Knobs		
1943-TB	Turnbuckles		
1943-TUBE	Cross Bars		
1943-TenB	Tension Block		
1943-2128-G	Gasket		
1943-2533-G	Gasket		
1943-2734-G	Gasket		
1943-3240-G	Gasket		
1943-GK	Cover Gasket		

Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.