OVERFILL PROTECTION VALVES AST/UST VALVE

Application:

Prevent overfills in AST's and UST's

Part Number - 49



Features-

- · No line shock, gradual shut-off
- No stress on system
- Prevents overfills reducing contamination and costly clean up.
- No need to specify remote or direct fill
- Compatible with fuel blends up to E85, diesel blends up to B20 and B100
- Can be pressure or gravity filled. Ideal for AST's that are below grade.


Construction-

- Anodized aluminum
- · Nickel plated steel
- FKM Seals



UNIVERSAL ADVANTAGE:

The best overfill protection available today. No line shock and gradual shut-off to eliminate any stress on the system. One part number -direct fill or remote fill. Compatible with gasoline and ethanol blends up to E85. Diesel and biodiesel blends up to B20 and B100.



U.L. Approved for both Pressure and Gravity Fill Applications. No Minimum Flow Rate Required.

Part Number	Fill adapter	weight	Α	В	<u>C</u>
49-02	2"	10lbs	22-3/8	3-11/16"	15-3/4"
49-03	3"	10lbs	22-3/8	3-11/16"	15-3/4"

Replacement Parts

<u>Part Number</u>	<u>Description</u>		
49-C-3	3x2 Fill Adapter		
49-C	2" Fill adapter		
49-CAP	2" Fill cap (sold seperatly)		
49-D	2" x 4" Adapter		
49-L	Adapter O-ring		
49-O	Replacemnt Float		
49-V	2" x12" Nipple		
49-44-B	44-B Adapter Gasket		
49-DTC	Drop Tube connector (sold seperatly)		

Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.